

# PAF

Business Unit or  
Division

Performance Additives and Fluids  
One Great Lakes Boulevard, P.O. Box 2200, West Lafayette, IN 47996-2200  
www.paf.greatlakes.com

Document Type

## Technical Data Sheet

Product Name

### Reolube<sup>®</sup> Turbofluid 46B

#### Typical Properties

Kinematic viscosity at 40°C	44 mm <sup>2</sup> /sec	ISO 3104
S.G. 20/20°C	1.155	ISO 3675
Pour Point	-21 °C	ISO 3016
Fire Point		
Autoignition Temperature		

Product  
Information

- Reolube Turbofluid 46B is a high performance, fire-resistant hydraulic fluid designed for use in electrohydraulic control systems of steam turbines. It may also be used for the lubrication of both steam and industrial gas turbines.
- Reolube Turbofluid 46B is based on a synthetic triaryl phosphate ester produced from butylated phenols, and has been formulated to meet the demanding requirements of the major steam turbine manufacturers.
- A data sheet, maintenance and use guide and a list of manufacturers' approvals are available on request.
- Reolube Turbofluid 46B is a Factory Mutual approved Group I fluid.

Handling and  
storage

- Wear gloves, overalls and eye protection.
- Store in original container in a cool dry place.
- Storage under suitable conditions will permit usage of the product for at least 12 months from the date of receipt.
- For additional handling and toxicological information, consult the GLCC Material Safety Data Sheet.